ProLite T1530SR-B1 | 15" touchscreen

ProLite 1530SR is based on the latest 5 Wire Resistive technology. Price / performance ratio is ideal for the budget conscious user while quality and specification is certainly not compromised. The display inputs include both Analogue and Digital (DVI) with Touchscreen connectivity via either USB or RS-232 which offers greater than typical flexibility. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree angles. Extensive Touch Utilities allow for 4 point calibration and either 9/25 point linerization. An incredibly powerful Touch solution.

Technical data

LCD Panel	**Panel**	TN Wide Angle
	LCD type	digital, colour TFT-LCD (active)
	Diagonal	15" (38 cm)
	Light transmittance	80 %
	Touchtech.	resistive
	Response time	16 ms
	Display area h x w	228.1 x 304.1 mm
	Pixel pitch h x v	0.297 x 0.297 mm
	Brightness	280 cd / m² with touch panel
	Contrast ratio	500 : 1 with touch panel
	Viewing zone	horizontal/vertical: 120°/100° right/left: 60°/60° up/down: 40°/60°
	Display colour	16.2 Million
	Native resolution	1024 x 768
Electronics	**Horizontal sync**	31 - 60 KHz
	Vertical sync	60 -75 Hz
	Bandwidth	80 MHz
	Input connector	D-SUB, DVI-D
	Plug and Play	VESA DDC2B™
	Synchronization	Separate Sync
Extras	**Interface**	RS-232C, USB
	Speaker	2 x 1W
	Included accessories	AC adapter, power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), user manual
User Controls	**Apple - Mac**	All iiyama monitors are compatible with Apple-Macintosh computers
	Controls	On-Screen-Display in 7 languages (D, GB, ESP, F, I, JP, Chinese) and 5 Front controls (Menu, Brightness, Volume, Input, Power)
	User controls	contrast, brightness, volume, auto tune, h-position, v-position, OSD language, clock, phase, colour temperature, input select, reset
	Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomie	**Safety**	CE, TÜV-SUD, FCC-B, UL / C-UL, VCCI-B
Power	**Power usage**	max. 23 W in normal use, max. 2 W in Power management mode
	Power supply	DC12V, 4A
	Power management	VESA DPMS
Mechanical	**VESA mounting**	75 mm
	Tilt angle	down 5°, up 90°
	Weight	4,3 kg
	Dimensions w x h x d	351 x 314.5 x 140 mm

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.

Megapixel describes the size of your desktop and therefore the amount of information your display can show. A lcd with a physical resolution of 9.2 mega pixels (3840 x 2400) can show 6 times more information than a display with 1.3 mega pixels (1280 x 1024). That means your desktop is about 600 percent bigger.